



# IN5327

IND3004DBPKG/US-100-DPV

Valve sensors



## Product characteristics

Inductive sensor

Rectangular, plastics

Quick disconnect

Sensing range 4 mm; [nf] non-flush mountable

## Electrical data

Electrical design	DC PNP
Operating voltage [V]	10...36 DC
Current consumption [mA]	15 (24 V)
Protection class	II
Reverse polarity protection	yes

## Outputs

Output function	2 x normally open
Voltage drop [V]	< 2.5
Current rating [mA]	250
Short-circuit protection	yes (non-latching)
Overload protection	yes
Switching frequency [Hz]	1300

## Monitoring range

Sensing range [mm]	4
Real sensing range (Sr) [mm]	4 ± 10 %
Operating distance [mm]	0...3.25

## Accuracy / deviations

Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2
Hysteresis [% of Sr]	1...15
Switch-point drift [% of Sr]	-10...10

## Environment

Ambient temperature [°C]	-25...80
Protection	IP 67

## Tests / approvals

EMC	EN 60947-5-2 EN 55011: class B
MTTF [Years]	1057

## Mechanical data

Mounting	non-flush mountable
Housing materials	housing: PBT; connector housing: stainless steel



IN5327

IND3004DBPKG/US-100-DPV

Valve sensors

Weight	[kg]	0.056
--------	------	-------


Displays / operating elements

Output status indication	LED	2 x yellow
--------------------------	-----	------------

Electrical connection

Connection	M12 connector; gold-plated contacts
------------	-------------------------------------

Wiring



Remarks

Pack quantity	[piece]	1
---------------	---------	---