# XZCP29P11L5

pre-wired connectors XZ - straight female - M12 - 8 pins - cable PUR 5m

Product availability: Stock - Normally stocked in distribution facility



Main	
Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	Application

Complementary

Complementary		
Electrical connection	Straight female connector M12, 8 pins	
Cable connector fixing	Screw-on	
Collar material	Stainless steel 316L	
Status LED	Without	
Cable length	16.40 ft (5 m)	
Cable outer diameter	0.20 in (5.2 mm)	
Cable composition	8 x 0.25 mm²	-
Wire insulation material	PUR	
[Ue] rated operational voltage	30 V AC 36 V DC	
Line Rated Current	2 A	
Contact resistance	5000 μOhm	
Minimum insulating resistance	1 GΩ	

### **Environment**

IP degree of protection	IP67	
Product certifications	CULus	
Ambient air temperature for operation	-31194 °F (-3590 °C) static 23194 °F (-590 °C) flexing	
Ambient air temperature for storage	-31212 °F (-35100 °C)	

### Ordering and shipping details

Category	22499 - SENSORS ACCESSORIES	
Discount Schedule	DS2	
GTIN	00785901591887	
Package weight(Lbs)	0.28 kg (0.61 lb(US))	
Returnability	Yes	
Country of origin	CZ	·

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl ph- thalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes

## Contractual warranty

Warranty	18 months

## Product data sheet Connections and Schema

# XZCP29P11L5

## Connections and Schemes

## Connectors



GY: Grey PK: Pink BU: Blue WH: White RD: Red BN: Brown GN: Green YE: Yellow